



Cold Work Tool Steel

Code: **CC**

Cylindrical recess material very suitable for production sector / mounting industry, especially mould production. Ensures compliance to usage with its suitable hardness surface brightness - stainless - flexibility, it is an essential product for equipment and tool production.

Cold work tool steel (Böhler) can be supplied with a wide variety and high quality selection from our company stocks. The desired hardness can be obtained with simple heat processing method as per request.

Hot Forming and Heat Treatment:

DIN 17006

- Forging Anneal : 1050 - 800°C
- Soft Anneal : 700 - 720°C
- Anneal Hardness : Max. 280 HB
- Stress Relief Annealing : 600°C
- Pre-Heat For Hardening : 650°C
- Hardening (Quenching) : Up to 12 mm at 780-800°C oil
Up to 12-20 mm at 780-800°C water
Up to 20-40 mm at 780-820°C water
Up to 40-60 mm at 810-830°C water
- Tempering : 180 - 200°C - 1 hour / 25 mm

Presented as: 2 Metre / as per request: 1 Metre

Order	Dia. mm	Kg/mt.
CC20	2.0	0.040
CC25	2.5	0.050
CC30	3.0	0.060
CC35	3.5	0.080
CC40	4.0	0.100
CC45	4.5	0.130
CC50	5.0	0.160
CC55	5.5	0.200
CC60	6.0	0.230
CC65	6.5	0.280
CC70	7.0	0.310
CC75	7.5	0.400
CC80	8.0	0.410
CC85	8.5	0.450

Order: **CC**. Diameter

Chemical Analysis:
% C1,15-CR 0,70-V 0,10

Material: 115 CR V 3
acc. to DIN 17006


Standard Ground Mould Plates

A	L	Thickness (t)																		
		27	37	47	57	67	77	87	97	107										
156	156																			
	196																			
	246																			
	296																			
	346																			
196	196																			
	246																			
	296																			
	346																			
	396																			
246	246																			
	296																			
	346																			
	396																			
	446																			
296	296																			
	346																			
	396																			
	446																			
	496																			
346	346																			
	396																			
	446																			
	496																			
	546																			
396	396																			
	446																			
	496																			
	546																			
	596																			
446	446																			
	496																			
	546																			
	596																			
	646																			
496	496																			
	546																			
	596																			
	646																			
	696																			
546	546																			
	596																			
	646																			
	696																			
	746																			
596	596																			
	646																			
	696																			
	746																			
	796																			



Ground Mould Plates Standard & Custom-made

Code: **EKP**



Precision machined and grinded plates are prepared as rectangular, square or as per request in the desired dimensions, also hole, pool, core space and similar processes can be done on plate, the desired precision tolerances excluding standard dimensions are applied. Surfaces are milled / precision perpendicularity and roughness are provided, precision surfaces ground plates with CK,45 / tool steel material are available in our stocks normatively or can be supplied in 2-3 working days. In addition, except our standard materials, the production in desired materials (alloy aluminium or quality steel material) is possible. All of these processes are produced within the structure of our company, then they are presented to our customers by providing cost saving. We are an accomplished and dedicated and customer oriented company with our experience and knowledge, advantages of being ahead and with our presentations of GTH Die & Mould Components improved by our side and needed by the whole world market and with unquestionable quality.

Order: **EKP. A x L x t**

Your standard order is selected from table or for your custom-made orders, technical drawing is required.

