


Date Stamp Plus

Code: FP...

Possibility for cooling circuits below the date stamp as they are removed from the front (with the EF). Inner insert is always at the same level as the body of the date stamp. Exact outer number positioning, Ideal clamping area.

Material: INOX 1.4034 Hardness: 51 ± 3 HRC

Max. working temp.: 150°



Options:






12 Months 12 Months + Year





Order: FP. (options) x A





Xtra Date Stamp

This is a permanent date stamp where only the central year insert is changed. The month is changed by using a screwdriver. Completely stainless. Only a H7 pocket required for assembly.

N

5

5

6

8

S

0.25

0.25

0.35

0.35

Material: INOX 1.4034 Hardness: 51 ± 3 HRC

Е

4

6

8

10

Order: FX. (options) x A

Max. working temp.: 100°

C

3.2

4.7

5.7

6.7

Α

6.0

8.0

10

12

- 0	pt	i۸i	าด
U	'nυ	IVI	10
	•		





12 Months

12 Months + Year





Code: IX..


Year


Xtra Insert for Date Stamp

Due to fact that the insert is adjustable / removable from the front of the mold, there is no need to remove the tool from the machine or disassemble the mould.

Material: INOX 1,4034 Hardness: 51 ± 3 HRC







Orde	С	
Arrow Only	Year	U
IX.3215SF	IX.3215	3.2
IX.4715SF	IX.4715	4.7
IX.5715SF	IX.5715	5.7
IX.6715SF	IX.6715	6.7

