



Flexible Cooling Hose

Code: **PSE**

Even at high pressures, it guarantees the directional stability. Resistant to all chemicals. Combine system with modular passing feature.

1/4" Operating Pressure:

6 Bar / Flow Rate 15 l. / min.

3/8" Operating Pressure:

6 Bar / Flow Rate 25 l. / min.

Order Code	Thread	Length
PSE.14	1/4"	280 mm
PSE.38	3/8"	320 mm

It can be supported with "Ball Valve" as per request.



O-Ring Set



- * 368 pcs.
- * 30 different sizes.
- * NBR Rubber resistant to oils and acids,
- * 60-90 hardness.

Content:

From Ø 3 to Ø 30 mm.

Thickness:

2 - 2.5 - 3 - 4 mm.

Order Code: **ORING.SET**

Cooling Adapter

Code: **DSN**



Order	Thread	Length	Hexagon
DSN.02	1/8"	22	14
DSN.03	1/4"	26	17
DSN.04	3/8"	26	22
DSN.05	1/2"	30	27

Teflon Sealing Tape

Order Code: **TEFLON**



12 Metre x 12 mm

Cooling Adapter

Code: **ONE**



Order	Thread	Length
ONE.01	1/8"-1/8"	21
ONE.02	1/8"-1/4"	23
ONE.03	1/4"-1/4"	23
ONE.04	1/4"-3/8"	23
ONE.05	1/4"-1/2"	29
ONE.06	3/8"-3/8"	23
ONE.07	3/8"-1/2"	29

Rubber Hose (gas & air)

Code: **HSG**

- * Double layer hoses with rope.
- * When ordering, specify desired meter.



Order	Inner	Outer
HSG.08	5	8.5
HSG.10	8	10.5
HSG.13	10	13.5
HSG.16	9.5	15.4
HSG.19	12.5	18.5

Liquid Gasket Sealant

* 300° heat resistance sealing.

Order Code: **SK404**

Red


Order Code: **SM404**

Blue



Reduction Fitting

Code: **DEN**



Order	Female	Male
DEN.01	G 1/8"	G 1/4"
DEN.02	G 3/8"	G 1/4"
DEN.03	G 1/8"	G 3/8"
DEN.04	G 1/8"	G 1/2"
DEN.05	G 1/4"	G 3/8"
DEN.06	G 1/4"	G 1/2"
DEN.07	G 3/8"	G 1/2"

Mini Ball Valve

Code: **KKV**



- * Manual controlled.
- * Button type ball valves.
- * 1/4 male threaded regulator.

Order Code	Female	Male
KKV.13	G 1/4"	G 1/4"
KKV.17	G 3/8"	G 3/8"
KKV.21	G 1/2"	G 1/2"
KKV.26	G 3/4"	G 3/4"
KKV.33	G 1"	G 1"

Thread & Pipe Sealant

Order Code: **678.511**



Gap Filling: 0.30 mm

Max. Thread: M80

Hand-tight: 20 - 40 minutes

Functional Hardening: 1 - 3 hours

Temp. Resistance: - 55°C to + 150°C

Usage Area:

It is a sealing product made of Teflon which is used in pipes and metals in which fluid passes through.

Cooling Fitting - Elbow

Code: **KDR**



Order	Male
KDR.10	G 1/8"
KDR.13	G 1/4"
KDR.17	G 3/8"
KDR.21	G 1/2"
KDR.26	G 3/4"
KDR.33	G 1"

Hose Clamp (stainless)

Code: **HKI**

Order Code	Capacity
HKI.1016	10 x 16
HKI.1220	12 x 20
HKI.1319	13 x 19
HKI.1623	16 x 23
HKI.2032	20 x 32



Repair Paste

Order Code: **SUNFIX**

It is especially for water leakage.

Easy to use and versatile problem solver paste for repair, maintenance and construction.

Cold-curing two-component paste suitable for sealing, bonding, moulding, repairing and filling.



Hose Fitting

Code: **HBE & HBF**



Order	Order	Male
HBE.6	HBF.6	6.0 mm
HBE.9	HBF.9	9.5 mm
HBE.13	HBF.13	12.5 mm
HBE.16	HBF.16	13.5 mm
HBE.19	HBF.19	18.5 mm

