



Flexible Cooling Hose

Code: **PSE**

Even at high pressures, it guarantees the directional stability. Resistant to all chemicals. Combine system with modular passing feature.

1/4" Operating Pressure:

6 Bar / Flow Rate 15 l. / min.

3/8" Operating Pressure:

6 Bar / Flow Rate 25 l. / min.

| Order Code | Thread | Length |
|------------|--------|--------|
| PSE.14 | 1/4" | 280 mm |
| PSE.38 | 3/8" | 320 mm |

It can be supported with "Ball Valve" as per request.



O-Ring Set



- * 368 pcs.
- * 30 different sizes.
- * NBR Rubber resistant to oils and acids,
- * 60-90 hardness.

Content:

From Ø 3 to Ø 30 mm.

Thickness:

2 - 2.5 - 3 - 4 mm.

Order Code: **ORING.SET**

Cooling Adapter

Code: **DSN**



| Order | Thread | Length | Hexagon |
|--------|--------|--------|---------|
| DSN.02 | 1/8" | 22 | 14 |
| DSN.03 | 1/4" | 26 | 17 |
| DSN.04 | 3/8" | 26 | 22 |
| DSN.05 | 1/2" | 30 | 27 |

Teflon Sealing Tape

Order Code: **TEFLON**



12 Metre x 12 mm

Cooling Adapter

Code: **ONE**



| Order | Thread | Length |
|--------|-----------|--------|
| ONE.01 | 1/8"-1/8" | 21 |
| ONE.02 | 1/8"-1/4" | 23 |
| ONE.03 | 1/4"-1/4" | 23 |
| ONE.04 | 1/4"-3/8" | 23 |
| ONE.05 | 1/4"-1/2" | 29 |
| ONE.06 | 3/8"-3/8" | 23 |
| ONE.07 | 3/8"-1/2" | 29 |

Rubber Hose (gas & air)

Code: **HSG**

- * Double layer hoses with rope.
- * When ordering, specify desired meter.



| Order | Inner | Outer |
|--------|-------|-------|
| HSG.08 | 5 | 8.5 |
| HSG.10 | 8 | 10.5 |
| HSG.13 | 10 | 13.5 |
| HSG.16 | 9.5 | 15.4 |
| HSG.19 | 12.5 | 18.5 |

Liquid Gasket Sealant

* 300° heat resistance sealing.

Order Code: **SK404** Red

Order Code: **SM404** Blue



Reduction Fitting

Code: **DEN**



| Order | Female | Male |
|--------|--------|--------|
| DEN.01 | G 1/8" | G 1/4" |
| DEN.02 | G 3/8" | G 1/4" |
| DEN.03 | G 1/8" | G 3/8" |
| DEN.04 | G 1/8" | G 1/2" |
| DEN.05 | G 1/4" | G 3/8" |
| DEN.06 | G 1/4" | G 1/2" |
| DEN.07 | G 3/8" | G 1/2" |

Mini Ball Valve

Code: **KKV**



- * Manual controlled.
- * Button type ball valves.
- * 1/4 male threaded regulator.

| Order Code | Female | Male |
|------------|--------|--------|
| KKV.13 | G 1/4" | G 1/4" |
| KKV.17 | G 3/8" | G 3/8" |
| KKV.21 | G 1/2" | G 1/2" |
| KKV.26 | G 3/4" | G 3/4" |
| KKV.33 | G 1" | G 1" |

Thread & Pipe Sealant

Order Code: **678.511**



Gap Filling: 0.30 mm
 Max. Thread: M80
 Hand-tight: 20 - 40 minutes
 Functional Hardening: 1 - 3 hours
 Temp. Resistance: - 55°C to + 150°C
Usage Area:
 It is a sealing product made of Teflon which is used in pipes and metals in which fluid passes through.

Cooling Fitting - Elbow

Code: **KDR**



| Order | Male |
|--------|--------|
| KDR.10 | G 1/8" |
| KDR.13 | G 1/4" |
| KDR.17 | G 3/8" |
| KDR.21 | G 1/2" |
| KDR.26 | G 3/4" |
| KDR.33 | G 1" |

Hose Clamp (stainless)

Code: **HKI**

| Order Code | Capacity |
|------------|----------|
| HKI.1016 | 10 x 16 |
| HKI.1220 | 12 x 20 |
| HKI.1319 | 13 x 19 |
| HKI.1623 | 16 x 23 |
| HKI.2032 | 20 x 32 |



Repair Paste

Order Code: **SUNFIX**

It is especially for water leakage. Easy to use and versatile problem solver paste for repair, maintenance and construction. Cold-curing two-component paste suitable for sealing, bonding, moulding, repairing and filling.



Hose Fitting

Code: **HBE & HBF**



| HBE | HBF | Order | Order | Male |
|-----|-----|--------|--------|---------|
| | | HBE.6 | HBF.6 | 6.0 mm |
| | | HBE.9 | HBF.9 | 9.5 mm |
| | | HBE.13 | HBF.13 | 12.5 mm |
| | | HBE.16 | HBF.16 | 13.5 mm |
| | | HBE.19 | HBF.19 | 18.5 mm |

