






















from our company.















Rpm: 60.000 Collet Ø: 3.0 mm

Dimensions: Ø 20 x Length: 160 mm

Hose Unit: Inclusive Weight: 140 g.



During Operation: Please operate with 2-3 drops of oil per minute.





During Operation:

Please use protective goggles, masks and ear plugs.

Rotary Air Grinder Tool Order Code: AG-360

High torque, silent and well balance. Ideal for precision grinding and finishing works. For applications such as grinding, milling, brushing and polishing with felts. During Operation: Please use protective goggles, ear plugs and masks.



Standard Accessories

Rpm: 60.000

Collet Ø: 2.35 mm - 3.0 mm

Dimensions: Ø 17 x Length: 159 mm

Hose Unit: Inclusive Weight: 130 a.



During Operation: Please operate with 2-3 drops of oil per minute.







During Operation:

Please use protective goggles, masks and ear plugs.

Rotary Air Grinder Tool Order Code: AG-460

High torque, heavy-duty, general purpose applicable on deburring, chamfering, milling, pre-polishing and finishing. Compact design and comfortable usage. During Operation: Please use protective goggles, ear plugs and masks.





Rpm: 35.000

Collet 0: 3.0 mm - 6.0 mm

Dimensions: Ø 22 x Length: 180 mm

Hose Unit: Inclusive Weight: 170 g.



During Operation: Please operate with 2-3 drops of oil per minute.







During Operation: Please use protective

goggles, masks and ear plugs.

Micro Rotary Air Grinder Tools



During Operation: Please operate with 2–3 drops of oil per minute.

Micro Types: Composite coated Air Tools,

aluminium body, non-skid coating, strong engine, high-speed and adjustable speed. In mould workshops and general grinding processes.

Order	Technical Information / 6,3 Bar	Price
DG-M5	Rpm: 54,000 • Collet Ø : 3 mm • Length: 134 mm Air Hose Ø : 8 mm • Weight: 200 g.	€ 70,00
DG-M	Rpm: 70.000 • Collet Ø : 3 mm • Length: 134 mm Air Hose Ø : 8 mm • Weight: 200 g.	€ 190,00
	Rpm: 82,000 • Collet Ø: 3 mm • Length: 134 mm Air Hose Ø: 8 mm • Weight: 200 g.	
ET-1	Rpm: 3.800 • Collet Ø: 6 mm • Length: 171 mm Air Hose Ø: 8 mm • Weight: 200 q.	€ 140,00

Rotary Air Grinder Tools (for mounted points)



Rpm: 35.000 Collet 0: 3.0 mm

Dimensions: (NAK-A90) Ø 19 x Length: 158 mm • Weight: 220 g. Dimensions: (NAK-A45) Ø 19 x Length: 162 mm • Weight: 250 g

Hose Unit: Inclusive

Accessories for Rotary Air Grinder Tool



Spare Collets

Collet Type	Order Code
Ø 2.35	AG-672
Ø 3.0	AG-673
Ø 6.0	AG-676
Ø 6.0	AG-676







Ø 30 Wheel

0 30 Rubber

0 30 **Abrasive**

Suitable Tools	Spare Part	Order Code
	Ø 30 Grinding Wheel	AGC01
AG-90 AG-45	Ø 30 Rubber Band	AGS01
	Ø 30 Abrasive Disc	AGP01



Weight: 200 g.

During Operation: Please operate




with 2-3 drops of oil per minute.







Hose Unit: Inclusive



Incompatible



Ultrasonic Polishing Machine

Order Code: U-LAP106

"U-LAP 106" can assist in reducing finishing time by up to 50% on hardened tools steel working on very small mould cavity & core details, extrusion dies and more. It is an advanced technological product realizing all diffucult works.

Power Source: AC 220 Ultrasonic Power: 45W, 2 levels Stroke Length: 10 - 35 mm Vibration: 15 - 25 khz

Dimensions: 152 x 100 x 72 mm



Corded Rotary Tool

Order Code: STRONG

With electronic cycle adjusted control unit, it starts with micro motor rotary tool at desired speed. It can work faster and serially with foot switch, desktop precision operations can be done with practical and powerful electronic machine. It is economical.

Rpm: 50.000 • **Collet Ø:** 3mm

50 hz / 220 V



Order Code	Specifications
BM21A	Rpm: 15.000 Power: 125 Watt
BM23A	Rpm: 25.000 Power: 200 Watt
BM26A	Rpm: 25.000 Power: 300 Watt
BM24A	Rpm: 22.500 Power: 500 Watt

Electrical Spiral Motor

Code: BM..A

Economical and modular for levelling and polishing.

Powerful motors provide facilities for users in levelling and polishing processes. Rotary spiral spring in Spiral Rod is only for tool to be used with 2.35 - 3 & 4 mm collets. However, in some cases, 6 mm collet also can be used softly / without pressing. To avoid rising heat at long uses, waiting at short intervals can be required. To provide continuance of work in uses, a spare Spiral Rod can be kept.

Note: Spiral Rod should be ordered separately.

Spare Parts

Order Code	Specifications
M19KK	Spiral Rod for Spiral Motor / 965 mm
M19FTK	Spiral Rod with Latch
YPØ	Spare Collets / 2.35 - 3 - 4 - 6 mm
BMW	Foot Switch for Spiral Motor (when ordering: specify current motor watt)

Hanger for Spiral Motor

Order Code: M18A



Foot Switch and cable connections of Electrical Spiral Motors are presented in packing. To use motor stably, we recommended you to use Hanger.

Page 342



Service and Spare Parts of all equipments are provided by our company.

190-Piece Economic Set



Polishing Kit / Multiple

Order Code: 6128001001

* Contents:

- Electrical Rotary Tool
- Grinding Wheels - Brushes
- Cutting Discs
- Wire Brushes
- Drills - Diamond Endmills
- Mounted Points
- Polishing Stones
- Mounted FeltsCollets
- Abrasive Rolls
- Diamond Compounds

* Tool Specifications:

- Power: 130 Watt- Voltage: 230 V- Frequency: 50 Hz.
- **Speed Control:** 1000 3000 Rpm - **Collets:** Ø16 mm / 2.4 mm - 3.2 mm

145-Piece Economic Set





Mini Polishing Kit

Order Code: 6128002001



- * Contents:
- Abrasive Rolls
- Cutting Discs
- Drills
- Diamond Endmills
- Polishing Stones
- Diamond Compounds
- Grinding Wheels
- Brushes
- Wire Brushes
- Mounted Points
- Mounted Felts
- Collets



EDM Polishing Stones

Code: EG..

EDM Polishing Stones are produced to make excellent levelling / polishing on rough surfaces. It takes the shape of the surface it works with by making fast cutting. It works precisely on figured surfaces. EDM Polishing Stones are suitable for manual and Air File Tool use. Hard and complex, especially in deep areas, long polishing stones can be selected. At flat and wide areas, short polishing stones can be less fragile by avoiding skidding.

When using by hand, use a holder. Different type holders at our Air File Tools present extensive usage opportunity.

For softer and clean polishing stone usage, you can use your polishing stone by steeping in low oil liquid etc. To use right graduation from coarse polishing stone to fine one on surface is important. Cleaning of operation area is also important.

EDM Polishing Stone Types

EGK	EGD	EGY	EGU	Grit	Operation
				# 120	
				# 150	Levelling
				# 180	
width x length (mm)	width x length (mm)	diameter x length (mm)	width x length (mm)	# 220	
- ' '	, , ,	, , ,		# 280	Pre-
4 x 4 x 100	6 x 3 x 150	Ø 6 x 150	8 x 8 x 150	# 320	polishing
6 x 6 x 150	13 x 3 x 150	Ø 8 x 150	10 x 10 x 150	# 400	
8 x 8 x 150	13 x 6 x 150	Ø 10 x 150	_	# 600	
				# 800	Finishing
10 x 10 x 150	-	Ø 12 x 150	-	# 1000	



Order: Type. Dimension. Grit

Order Example: _______ EGK. 4 x 4 x 100. 320

EDM Polishing Stone Holders

	Manually Operated			Air File Tool Operated						
Product										
Capacity	6 x 3	13 x 3	4 - 6	8 - 10	13 x 3	13 x 6	AR-	AR-	AR-	AR-
Order Code	GT-	613	GT-468		GT-133		661	667	666	662



Polishing Block Stone Code: BG...

For wide surface levelling and chamfering / deburring. **EKR:** General Steel • **SCG:** Hard Steel

Order Example	Α	Н	L
BG100. EKR or SCG	16	25	100
BG125. EKR or SCG	20	40	125
BG150. EKR or SCG	25	50	150
BG200. EKR or SCG	25	50	200



Mini Cutting Disc

Code: **K5..**

It is used in cutting operation of all metals including hard steels at Rotary Tools.

Order Code	d	k	Mandrel
KS25	25	0.65	g 0 05
KS40	40	1.0	Ø 2.35 mm Ø 3.0 mm
KS60	60	1.5	0.0111111



Fiber Ceramic Polishing Stones

ode: SG

"SG" Fiber Ceramic Polishing Stones are the excellent stones for detail polishing. They preparead by pressing with resin binder spraying screened, gauged micron diamond particles on powerful fiber textured ceramic, "SG" Ceramic Stones have the feature of resistance with flexible structure againts breakage.

Optimal for premium polishing of flat surfaces, hard to reach slots, ribs and corners. High polishing productivity can be obtain without clogging. "SG" Ceramic Stones can be used in our Air File Tools or by hand (please see below for manual holders).

Fiber Ceramic Polishing Stones Types

Grit	Code		
CSC	# 180		
CSO	# 250		
CSD	# 280	Thickness: 1 mm	Diameter: 3 mm
CSN	# 360	Width x Length	Diameter
CSB	# 400	1 x 4 x 100	
CSY	# 700	1 x 6 x 100	Ø 3 x 100
CSR	# 1200	1 x 10 x 100	

Order: SG. Grit Code. Dimension Order Example:
SG. CSO. 1 x 6 x 100

Fiber Ceramic Polishing Stone, Manual Holders



"Strong Fiber Texture & Durable Structure"









"SG" Ceramic Stones suitable to be used in Air File Tools. Refer to "page-341" for Air File Tools.







Shank Dia, 3 mm

612A

6 x 12

80B

Ø 8

616J

6 x 16

816K

8 x 16

Order: SPT. Code

Mounted Points

D

Ø 3 mm

256A

2.5 x 6

30B

ØЗ

310T

3 x 10

815P

308A

3 x 8

40B

Ø 4

412T

4 x 12

1018P

10 x 18

410A

4 x 10

50B

Ø 5

710T

7 x 10

412K

4 x 12

510A

5 x 10

60B

Ø 6

412J

4 x 12

515K

5 x 15

Form

A/R Shank

3 mm

Code:

D x L

Form

Shank

3 mm

Code:

D x L

308T

3 x 8

612P

6 x 12

Order Example: -

816A 1016A

10 x 16

120B

Ø 12

1016J

10 x 16

133E

13 x 3

8 x 16

100B

Ø 10

816J

8 x 16

132E

13 x 2

813R

8 x 13

1224R

12 x 24

609S

6 x 9

162E

16 x 2

SPT, 410A

Pink Mounted Points

(Code: SPT)

"SPT" Mounted Points are suitable to soft and hard surfaces. With formation of aluminium oxide & ceramic grain textured in fast material removal feature, the mounted points provide the desired performance on all kinds of surfaces. After process, it can be ready for polishing by cleaning off point traces on surface with Rubber Mounted Polishing Points.

There should be at least 10 mm fastening length at collet. Operation should be soft without pressing.

Cutting speed max.: 50 m / s. Calculation:


 $n = V (m/s) \times 60.000$

 $D = (mm) \times 3.14$

Mounted Points Shank Dia. 6 mm



Form B Shank 6 mm	D L ww 9 0							
Code:	1015B	1620B	2020B	2030B	2040B	2525B	2532B	3240B
DxL	10 x 15	16 x 20	20 x 20	20 x 30	20 x 40	25 x 25	25 x 32	32 x 40



Form E Shank 6 mm								
Code:	0816E	1230E	1640E	2030E	2040E	2525E	2540E	3240E
DxL	8 x 16	12 x 30	16 x 40	20 x 30	20 x 40	25 x 25	25 x 40	32 x 40

	Form G/H/J Shank 6 mm								
	Code:	2016G	2520G	10H	15H	20H	1225J	1632J	2040J
Ĭ	DxL	20 x 16	25 x 20	Ø 10	Ø 15	Ø 20	12 x 25	16 x 32	20 x 40







Grinder Disc

Because it is circular, it is mostly used at thread ranges, cutting tool edges and mould / machine production.

Order Code Specification			
DP25	Ø 25 x thickness: 3.2 mm / 80 Grit		
VM03	Mandrel / 2.35 & 3.00 mm		



Mounted Wire Brushes

These products are very successful in cleaning EDM and deep burrs traces (especially with Guvenal - Diamond Compound Order Code: SDP14).





As per request: Shank 2.35 mm is available.







Self-adhesive Abrasive Disc

For Abrasive:

Order: DZ.. x Grit Order Example: DZ18 x 320

For Holder:



Order: DZL.. x Shank Order Example: DZL80 x 3

Code	Abrasive	Grit	Holder	Shank
DZ10	Ø 10		Ø 10	
DZ18	Ø 18	# 80	Ø 18	
DZ30	Ø 30	# 120	Ø 30	3 mm
DZ45	Ø 45	# 220	Ø 45	
DZ70	Ø 70	# 320	Ø 70	6 mm
DZ80	Ø 80	# 400	Ø 80	
DZ100	Ø 100		Ø 100	



Mini Abrasive Roll Set Code: ML

Mini Abrasive Rolls & Holder.

It is sold in package: 5 + 5 coarse / fine grit and holder (10 pcs abrasive + 1 pcs holder).

Shank 3 mm

-60

	D
'	'L'

Order Code	Abrasive	Grit
ML04	Ø 4 x 15 mm	
ML05	Ø 5 x 15 mm	# 120 (5 pcs.)
ML06	Ø 6 x 15 mm	, , ,
ML08	Ø 8 x 20 mm	# 320 (5 pcs.)
ML10	Ø 10 x 20 mm	, , ,



As per request / Custom-made orders.







Mini Abrasive Rolls

Order: Code, Grit Order Example: SPZ12.80

Code	Abrasive	Grit
SPZ12	Ø 12 x 25	
SPZ15	Ø 15 x 25	# 80
SPZ20	Ø 20 x 30	
SPZ25	Ø 25 x 30	# 100
SPZ30	Ø 30 x 30	# 120
SPZ40	Ø 40 x 30	# 220
SPZ50	Ø 50 x 30	# 220
SPZ60	Ø 60 x 35	

Holder for Abrasive Rolls

Order Code	Holder	Shank - Length
SPL12	Ø 12	Ø 6 - 60
SPL15	Ø 15	Ø 6 - 60
SPL20	Ø 20	Ø 6 - 60
SPL25	Ø 25	Ø 6 - 60
SPL30	Ø 30	Ø 6 - 60
SPL40	Ø 40	Ø 6 - 65
SPL50	Ø 50	Ø 6 - 65
SPL60	Ø 60	Ø 6 - 65




Rubber Mounted Polishing Point Rubber, Soft Type & Finishing

Form RK Shank 3 mm					
Order:	RK04	RK05	RK06	RK08	RK10
DxL	4 x 13	5 x 15	6 x 17	8 x 20	10 x 20

Form RB Shank 6 mm					
Order:	RB15	RB20	RB25	RB30	RB35
DxL	15 x 25	20 x 25	25 x 25	30 x 30	35 x 35



Rubber Mounted Polishing Point Ceramic, Hard Type & Pre-polishing



ш						
	Form CB Shank 6 mm					
	Order:	CB15	CB20	CB25	CB30	CB35
	DxL	15 x 25	20 x 25	25 x 25	30 x 30	35 x 35



Polishing Rubbers

Cylinder (Ø6x22) Order: Disc (Ø20x3) Order: Red (medium) : KK06 Red (medium) : DK06 Black (hard) : KS06 Black (hard) : DS06 : DM03 : VM03 Mandrel Mandrel









Order: SPK. Code


- Order Example: — SPK, 1014A


Mounted Polishing Felts

Shank Dia, 3 mm









Adhesive Felt Discs Code: Y..D



	Order	Dimension	Hole
ı	Y18D	Ø 18 x 4 mm	7 mm
ı	Y30D	Ø 30 x 4 mm	12 mm
	Y45D	Ø 45 x 4 mm	18 mm

Page 346

"Y..D" Adhesive Felt Discs suitable to be used with "DZL" Holders. Refer to "page-345" for "DZL" Holders.


Mounted Polishing Felts


Code: SPK


It is used at finishing with Diamond Compounds. Also, it can be applied with other polishers. Even it is used at very high cycles, it does not burn. Our felts are produced as double layer fired. In operation, avoid extreme high pressing.

Mounted Polishing Felts

Shank Dia, 6 mm









Mounted Felt Sticks Code: S..D.

Usage with Electrical or Air Tools.

Order Code	Dimension	Shank
S06D	6 x 6 x 25 mm	a .
S10D	10 x 10 x 35 mm	Ø3 mm
S12D	12 x 12 x 45 mm	



Felt Polishing Sticks Code: E..K

Suitable for manual usage.

Order Code	Dimension
E06K	6 x 6 x 150 mm
E10K	10 x 10 x 150 mm
E12K	12 x 12 x 150 mm
GT-133	Holder (suitable for tool usage)



Polishing Felt Sheets Code: P...

It can be adhered to your tool by cutting.

Order Code	Dimension ———		
P325	6 x 250 x 250 mm		
P625	10 x 250 x 250 mm		
P1025	12 x 250 x 250 mm		



Mounted Hair Brushes

Code: SKF

Mounted Hair Brushes facilitating polishing process and not requiring extra tool. These brushes form the perfect surface with fine micron Diamond Compounds at final polishing.













Plexiglass Polishing Sticks

Code: PC...

It becomes a precision Diamond File when used with Diamond Compounds. GT-133 is a suitable holder for tool usage.

Order Code	Dimension	Type
PC.08	8 x 8 x 150 mm	Square
PC.10	10 x 6 x 150 mm	Rectangular
PC.13	13 x 6 x 150 mm	Rectangular
PC.06	Ø 6 x 150 mm	Round
GT-133	Holder (suitable for tool usage)	





Wooden Types

Code: ASK

It is suitable to polish with Wooden Felts at narrow and radius areas of moulds, areas unsuitable to use polishing stones.

Mounted Wooden Points

Wood	len l	Lapi	pina	Stic	ks

Order Code	Dimension	Order Code	Dimension	Type	
ASK.06	Ø 6 x 15	AC.06	6 x 6 x 150	Square	
		AC.10	10 x 10 x 150	Square	
ASK.10	Ø 10 x 20	AC.12	12 x 12 x 150	Square	
ASK.15	Ø 15 x 25 Ø 20 x 30	AC.03	6 x 3 x 150	Rectangular	
		AC.13	13 x 6 x 150	Rectangular	
ASK.20		AC.20	20 x 8 x 150	Rectangular	
ASK.010	Ø 10 (spherical)	ACS.6	Ø 6 x 150	Round	
		ACS.8	Ø 8 x 150	Round	



Diamond Compounds

(order code: SDS200).

Code: SDP

Our Diamond Compounds have been formulated using a blend of high quality diamond grit, polisher chemical mixture and herbal oil. It is highly concentrated. Economical price and in box packaged as 20 g. syringe. From rapid stock removal process to final polishing process, it cleans EDM traces in hard areas by removing burrs (stock removal). Our Diamond Compounds are soluble in both oil and water. During operation, the compound may get lumpy / dry, in this case, it can be moisturised with 1-2 drops of Diamond Compound Moisturiser

Order Code	Micron (µm)	Approx. Mesh	Content	Application	
SDP.01	0/1	#60.000	20 g.		
SDP.02	2/1	#14.000	20 g.	Final	
SDP.03	3/2	#8.000	20 g.	Polishing	
SDP.05	5/3	#4.000	20 g.		
SDP.07	7/5	#3.000	20 g.		
SDP.10	10 / 7	#1.700	20 g.	Pre-	
SDP.14	14 / 7	#1.500	20 g.	polishing	
SDP.20	20 / 14	#1.100	20 g.		
SDP.28	28 / 20	#800	20 g.	Rapid	
SDP.40	40 / 28	#550	20 g.	Stock	
SDP.60	60 / 40	#500	20 g.	Removal	

Application: Application is usually done with circular movements. During operation, cleaning is very important and it absolutely should be done at every stage. The sequence should be followed from coarse to fine micron. Polishing tools for each micron compound should be specified and should be used only at that micron, absolutely don't mix with other micron compounds. For cleaning of mould surface, our Cleaning Spray (order code: W170104) is an effective, economic and provide easiness. As a surface protector our new product (**order code**: W160113) is perfect as flexible surface coating.

Diamond Compound Moisturiser

Order Code: SDS200


During operation, the compound may get lumpy / dry, in this case, it can be moisturised with 1-2 drops of Diamond Compound Moisturiser.

Content: 200 q.



Metal Polisher Paste

Metal work pieces lose their gloss in time and can be oxidized. In this case, Metal Polisher Paste cleans surfaces and purifies from rust and dirt's. It is a very good dirt remover, it does not remove burrs and only cleans and polishes.










Tapered Abrasive Cartridge Rolls

It is ideal for grinding in limited and narrow areas. When the outermost abrasive is worn down, non-worn abrasive found is lower layers appears.

Application: Please always grind by using tip instead of surface. During operation, wear protective goggles. Cutting speed: 11 m / s max.

Code	Abrasive	Grit
RZ06	6 x 38	" 00
RZ10	10 x 38	# 80
RZ13	13 x 38	# 120
RZ16	16 x 38	# 220
R720	20 x 38	π Ζ ΖΟ

Mandrel Code 3 x 30 TM03 TM06 6 x 60



Order Example: RZ16, 220



Abrasive Cloth Rolls

Code: BZ

Order Code	Grit	Operation	Width	Package		
BZ40	#40					
BZ60	#60					
BZ80	#80	Coarse				
BZ100	#100			1 Metre		
BZ120	#120					
BZ150	#150		150 mm			
BZ180	#180					
BZ220	#220	Medium				
BZ280	#280					
BZ320	#320	Fine				
BZ400	#400					
BZ600	#600					
BZ800	#800					




Waterproof Abrasive Paper

Waterproof Abrasive Laper				
Order Code	Grit	Operation	Dim.	Package
SZ40	#40			
SZ60	#60			
SZ80	#80	Coarse		1 pcs,
SZ100	#100			
SZ120	#120			
SZ150	#150		230 x 280	
SZ180	#180			
SZ220	#220	Medium	x 28	
SZ280	#280		80 n	pos.
SZ320	#320		mm	
SZ400	#400			
SZ600	#600		Fine	
SZ800	#800	Fine		
SZ1000	#1000			
SZ1200	#1200			



Clip-on Abrasive Disc Code: KZD



Abrasive Disc


Code	Disc	Grit
KZD38	Ø 38	# 36
KZD51	Ø 51	# 80
KZD76	Ø 76	#120


Mandrel

Order Code	Shank	Rubber Ø			
KLT63	6 mm	38 mm			
KLT65	6 mm	51 mm			
KLT67	6 mm	76 mm			



Order Example: KZD51.80





Abrasive Mop Whells


Code: MZ

During operation, wear protective goggles. Cutting speed: 15 - 20 m/s max.

Code	D	L	d	lı	Grit
MZ3.1515	15 15	15	3.0	40	
MZ3.2020	20	20		40	#40
MZ6,2015	20	15		40	
MZ6.2020		20		40	#60
MZ6.2515	25	15		40	#80
MZ6.2525		25		40	"400
MZ6.3015	30	15		40	#100
MZ6.3025		25		40	#120
MZ6.4020	40	20	6.0		#180
MZ6.4030	40	30			#100
MZ6.5020	E0.	20		40	#220
MZ6.5030	60	30		40	#320
MZ6,6020		20		40	
MZ6.6040		40		40	#400
MZ6.8040	80	40		40	



Order Example: MZ6.2515 x 80



Waterproof Abrasive Paper with Sponge Code: SM

Order Code	Grit	Width	Package	
SM150	#150			
SM220	#220		1 Metre	
SM280	#280	115 mm		
SM320	#320	111111	Mene	
SM400	#400			





All sides of the product can be used. Easy to clean, you can use repeatedly.

Foam - Abrasive Pads Code: EZ

Order Code	Grit	Dimension	Package
EZ60	#60	100	
EZ100	#100	×	
EZ150	#150	68 x	pcs.
EZ220	#220	27 mm	poo.
EZ320	#320		

Carbide Rotary Burrs







Order Example: **SA14. B**









Shape B: Double cut for general purpose use. Improves control and reduces chips. The cross toothing provides a higher cutting capacity compared with the simple toothing.

Shape A: Standard cut for general operations.

Shape C: Diamond cut for hardest materials and finest finishes. Shape D: Aluminium toothing. Usage area; non-ferrous metals, aluminium, brass, copper, diecasts, zinc and plastics. To debur, break edges, trim and surface machining.





During Operation: Please use protective goggles, masks and ear plugs.



Cylinder Type DIN 8033

Code: SA

טניטט אווע	2000										
Code	d d1		L1	L	Shape						
SA42	2.5	3	11	38							
SA43	3.0	3	14	38	В						
SA14	5.0		16	50	А						
SA1	6.0	6	16	50	С						
SA3	9.5	U	19	63	D						
SA5	12.7		25	69							



Cylinder Type with Endcut

Code: SB

Code	d	d1	L1	L	Shape	
SB42	2.5	3	11	38		
SB43	3.0	3	14	38	В	
SB14	5.0		16	50	Α	
SB1	6.0	6	16	50	С	
SB3	9.5	0	19	63	D	
SB5	12.7		25	69		



Radius Cylindirical Type

Code: SC

Code	d	d1	L1	L	Shape	
SC42	3.0	3	14	38		
SC42ML2	3.0	3	14	50	В	
SC14	5.0		16	50	Α	
SC1	6.0	6	16	50	С	
SC3	9.5	0	19	63	D	
SC5	12.7		25	69		



Ball Type

Code: SD

Code	d	d1	L1	L	Shape	
SD41	2.5	3	2.3	38		
SD42	3.0	3	2.5	38	В	
SD14	5.0		4.0	50	Α	
SD1	6.0	6	5.0	50	C	
SD2	8.0	6	6.4	50		
SD3	9.5		8.0	52		



Pointed Tree Type

Code: SG

Code	d	d1	L1	L	Shape
SG41	3.0	3	6.0	38	
SG43	3.0	3	9.5	38	В
SG1	6.0		16	50	Α
SG2	8.0	6	19	63	С
SG5	12.7	0	25	69	D
SG6	16		25	69	



Flame Type

Code: SH

Code	d	d1	L1	L	Shape
SH41	3.0	3	6.3	38	
SH41ML	3.0	3	6.3	50	В
SH1	6.0		9.5	50	А
SH2	8.0	6	19	63	С
SH5	12.7	6	32	76	D
SH6	16		36	80	



Radius Cone Type


Code: SL

riadido (00	odo. OL			
Code	e d d1 L1		L1	L	Shape
SL41	3.0	3	9.5	38	
SL42	3.0	3	12.7	38	В
SL1	6.0		16	50	Α
SL2	8.0	6	22	69	С
SL4	12.7	6	28	76	D
SL6	16		33	80	



90° Cone Type

Code: SK







CBN Grinding Points

Code: PEF

These grinding points produced with electroplated method. They are designed for shaping and finishing hard materials including Tungsten Carbide and Ceramics. It is used at mould processing, mostly polishing runners or lapping other channels / holes areas making burrs and finishing. Shank: Ø3 mm • Full Length of Products: 45 mm



- Order Example: PEF. 50B

Shank: 3 mm Full Length: 45 mm		100000000	8888888						
Code:	10A	15A	20A	25A	30A	35A	40A	50A	30 V
DxL	1x8	1.5x8	2x8	2.5x8	3x10	3.5x10	4x10	5x10	3x10
				1000		4.31			

Å	A		(65656569	(SESSER)		H			
20B	30B	50B	15C	20C	25C	30C	35C	40C	50C
Ø 2	Ø 3	Ø 5	1.5x8	2 x 8	2.5x8	3x10	3.5x10	4x10	5x10

			8896			Carococks	Garactico (Constitution of the Constitution of	E-reseases	(88888888)
20F	30F	50F	20P	30P	15R	20R	30R	20T	30T
2x10	3x10	5x10	2x12	3x15	1.5x10	2x12	3x14	2x10	3x10

40Q	30S	40S
4 x 7	3 x 6	4 x 8



Diamond CBN Set - 30 pcs.

Order Code: BMS-30



Contains one each of below:

PEF-10A, 15A, 20A, 25A, 30A, 35A, 40A, 50A, 20B, 30B, 50B, 15C, 20C, 25C, 30C, 35C, 40C, 50C, 20P, 30P, 15R, 20R, 30R, 30S, 20F, 30F, 50F, 20T, 30T and 30V.

Diamond CBN Set - 20 pcs.

Order Code: BMS-20

Contains one each of below:

PEF-10A, 15A, 20A, 25A, 30A, 35A, 15C, 20C, 25C, 30C, 20P, 30P, 15R, 20R, 30R, 20B, 30B, 20F, 30F and 20T.

Diamond CBN Set - Economic

Order Code: T20 20 pcs.

Order Code: T30 30 pcs.



* Contents are the same as the BMS Set.

Diamond CBN Set 50 pcs. - Economic

Order Code: C280300




Needle File Set -12 pcs.

Order Code: BSE12

Bahco

Contains one file each of:

Hand, flat, triangular, square, half round, crossing, round, knife, barrette, slitting, round-edge joint and marking. Type of cut: Fine, medium & coarse. * 3 x 160 mm



Needle File Set - 6 pcs.

Order Code: BSE06 Bahco

Contains one file each of: Hand, flat, half round, round, triangular and square. Type of cut: Medium * 3 x 160 mm



Needle File Set - 6 pcs.

Order Code: 1720

Contains one file each of: Hand, flat, half round, round, triangular and square. Type of cut: Medium

* 3 x 160 mm


Beta


Needle File Set - 10 pcs. **Economic**


Order Code: SE10

Type of cut: Medium * 3 x 140 mm













Code	Inch	Cut	Ø	L
YTE100	4"		Ø 4	100
YTE150	6"	Coarse	Ø 6	150
YTE200	8"	Medium	Ø 8	200
YTE250	10"	Fine	Ø10	250
YTE300	12"		Ø12	300




300

12"

UTE300





Engineers File - Square



Engineers File - Aluminium


Plastic Handle for Files








Steel Needle File - Round



Code: SYF











Diamond File Set - 5 pcs.

Order Code: RKE1005

Contains one file each of:

Flat, triangular, square, half round and crossing.



Diamond File Set - 10 pcs.

Order Code: 13710 * 4 x 160 mm



Diamond Course File Set

5 pcs. * 4 x 160 mm


Order Code: 13711

Die Sinkers Diamond Riffler File Set - 5 pcs.

Order Code: 13726

* 3 x 140 mm








Diamond Files


Economic Series



Order Code	Shank	d x L1 x L
ELE140	Ø4	5 x 70 x 140
ELE160	Ø5	8 x 50 x 160
ELE200	Ø5.5	8 x 70 x 200

Diamond File - Half Round

Code: EYY



Diamond File - Round

Code: EYE



Order Code	Shank	d x L1 x L
EYE140	Ø4	Ø 3 x 70 x 140
EYE160	Ø5	Ø 4 x 50 x 160
EYE200	Ø5.5	Ø 4 x 70 x 200

Diamond File - Square

Code: DEE



Order Code	Shank	d x L1 x L
DEE140	Ø4	3.0 x 70 x 140
DEE160	Ø5	3.6 x 50 x 160
DEE200	Ø5.5	3.6 x 70 x 200

Diamond File - Triangular

Code: UEE



Order Code	Shank	d x L1 x L
UEE140	Ø4	3.7 x 70 x 140
UEE160	Ø5	5.0 x 50 x 160
UEE200	Ø5.5	5.0 x 70 x 200

Diamond Tapered Files - Hand

Code: CF..

Order Code	Cross Section	Diamond Length	Total Length
CF503	6.1 0.6	60 mm	
CF502	8.2 0.6	60 mm	180 mm
CF501	10.2 0.7	70 mm	

Diamond File - Round

Order Code: IF503



Shank	Cross Section	Length
5 x 5	5.2	Diamond: 80 mm Total: 215 mm



Shank Cross Section Length Diamond: 80 mm			
Diamona. 00 mm	Shank	Cross Section	Length
11 X 4 /14.0 Total: 215 mm	11 x 4	9.0-	Diamond: 80 mm Total: 215 mm

Diamond File - Flat

Order Code: IF501

Shank	Cross Section	Length
11 x 4	-11.0- 4.0	Diamond: 80 mm Total: 215 mm

Diamond File - Triangular Order Code: IF505

	Shank	Cross Section	Length
			Diamond: 80 mm
	11 x 4	-8.0-	Total: 215 mm
\			

Diamond File - Square

Order Code: IF504

Shank	Cross Section	Length
6 x 6	6.0	Diamond: 80 mm Total: 215 mm


Diamond File with Handle - Flat

Order Code: HX4


Cross Section **Total Length** 12.2-100 mm (4")

Diamond File with Handle - Flat

Order Code: HX10


















Diamond File Set - 5 pcs.










Diamond Tapered File Set



Tool Post Grinders

Code: ST..


On Lathe / for Internal & External Grinding

It is an excellent machine for internal / hole grinding with easy to mount to the lathe. During the internal works, it maintains many diffucult operation, in addition to external grinding operation together.

- 15 / 20% material removal.
- Internal grinding up to 150 mm (up to 600 mm with additional apparatus).
- Surface / flat grinding operation with Cup Grinding Wheel.

The installation is made by placing a flange on the part of the lathe where the tool holder is located. As all lathes have different axis, the lathe axis is referenced. You can request assistance from our company for installation and training.





Specification	Order Code: ST175
Motor Power	0.5 HP / 380 V ~ 50 Hz
Rpm	2800
Grinding Wheel	175 x 20 x 20 (25 / 32)
Suitable Lathe	1000 and 1500 mm

Specification	Order Code: ST201
Motor Power	1 HP / 380 V ~ 50 Hz
Rpm	2800
Grinding Wheel	200 x 20 x 20 (25 / 32)
Suitable Lathe	2000 mm

Specification	Order Code: ST202
Motor Power	2 HP / 380 V ~ 50 Hz
Rpm	3000
Grinding Wheel	200 x 20 x 20 (25 / 32)
Suitable Lathe	2000 mm and over





Polishing & Cleaner Block

Code: KS..

It is for lapping, polishing and cleaning. Polishing & Cleaner Block is a multi-purpose abrasive cleaner, impregnated throughout with sharp abrasive grit, Removes light rust or tarnish restoring a bright metal finish.

Suitable for dry or wet use.

Block Dimension: $80 \times 50 \times 20 \text{ mm}$.

Extra Coarse - 36 grit (wine)
Coarse - 60 grit (blue)
Medium - 120 grit (grey)
Fine - 240 grit (brown)



- Order Example: KS. 60





Mini Abrasive Pen

Code: **KZ310**

It provides opportunity to use each sides of abrasive by pressing tension spring and turning abrasive band. It is suitable to use at areas that are hard to reach. Multi-purpose usage area at hard operations, it is most suitable equipment to use instead of file. Total length: 158 mm.

Spare Abrasive Bands:

It can be purchased in packages containing 10 pieces (#180 / #320 grit, 5+5 pcs).

Mini Abrasive Rod:

Order: KZ310

Spare Abrasive Bands:



Order: ZK155



Work Safety Products for Mould Polishing Operation

Order Code	Product
KBK	Ear Protection
KLK	Earplug
STM	Dust Mask
VTM	Dust Mask with Valve
KG01	Safety Goggles



Table Lamps with Magnifier & Hand Magnifier with Lamp

Order Code	Specifications
ZLA	Diopter: 5 / Glass Lens Dimension: 190 x 157 mm Light Source: 2x 9W fluorescent lamp / Voltage: 220V - 240V
MBL	Diopter: 5 / Glass Lens Dimension: Ø 88 mm Light Source: LED / Voltage: 220V
TROY	Hand-held / Zoom: 6x / Light Source: LED / Battery: AA

Clear Loupe Magnifier

Order Code: 183303



Magnification Power: 15x

This pocket magnifier is ideal for a variety of measuring tasks. Transparent draw tube enables clear imaging of the workpiece.

Headband Magnifier

Order Code: HL-09



Magnification Power: 2.5x

Light and impact resistant plastic frame. Comfortable padded headed and fully adjustable.

Mini Vacuum Base Vice

Order Code: RMM0201



Jaw Width:
70 mm
Jaw Opening Max.:
70 mm
Weight:
1.25 kg

Vacuum base mounts on any smooth surface for workholding where you need it. Vice can be rotated 360-degree. Supplied with removable soft rubber protective jaw covers.

Inspection Mirror

Order Code: 1714



It is used to get images from areas that are hard to see. Light and impact resistant plastic frame.

Diameter: 25 mm Length: 155 mm Weight: 6 g.



Tool Cabinet with Drawers

Code: HOBI...

The products used in polishing operation absolutely should be stored separatelly. In order not to mix products and to protect regularly, we are recommended our cabinets.

Order Code: HOBI-114

Dimensions	Number of Drawers
400 x 220 x 660 mm	22

Order Code: HOBI-113

Dimensions	Number of Drawers
400 x 220 x 500 mm	19



Industrial Cleaning Cloth Roll

It is produced completely from cellulose and absorber. It is excellent for cleaning of precision tools without leaving a trace. It does not leave feathers, not easily torn and practically used.

Stand Dimension: 450(l) x 330(w) x 940(h) Stand Weight: 2.5 kg • Cloth Weight: 11 kg

Cloth Length: 350 metre Cloth Width: 25 cm

Order Code	Product
P350	Cleaning Cloth Roll (350 metre)
P1000	Cloth Stand + Cloth Roll Set

